

# ENDURO FACTORY 4 STROKE MY27

DATA SHEET	250 SEF	300 SEF	450 SEF	500 SEF
Motor	4-stroke DOHC, 4-valve SHERCO technology			
Displacement	248,43cc	303,68cc	449,40cc	478,22cc
Bore and stroke	78 x 52,20 mm	84 x 54,80 mm	95 x 63,40mm	98 x 63,40 mm
Fuel supply	Synerject electronic injection			
Cooling	Liquid cooling with forced circulation			
Starting	Electric starter			
Battery	Skyrich 12V 140A Lithium			
Exhaust	Complete Akrapovič exhaust system			
Transmission	6-speed transmission – gear drive primary and chain drive secondary			
Clutch	Hydraulic, multi-disc in oil bath			
Ignition	220 W Alternator			
Chassis	Semi-perimetric high-strength chrome-molybdenum steel			
Fuel tank	9,8 L capacity			
Brakes	Brembo hydraulic brakes, 260 mm Ø (front) - 220 mm Ø (rear)			
Front suspension	Closed cartridge KYB fork with (Factory range) settings and spring rates specific to each model. 48 mm Ø fork legs - 300 mm stroke			
Rear suspension	KYB 50 shock absorber with hydraulic settings and spring rates specific to each model 18 mm Ø - 330 mm stroke			
Front wheel	1.60 x 21" black anodized Excel rim, Michelin Enduro tire			
Rear wheel	2.15 x 18" black anodized Excel rim, Michelin Enduro tire			
Wheelbase	1480 mm		1490 mm	
Ground clearance	355 mm			
Saddle height	950 mm			

